

Guest Network

AiProtection

Adaptive QoS

Traffic Analyzer

USB Application

AiCloud 2.0

Advanced Settings

Wireless

LAN

WAN

IPv6

VPN

Firewall

Administration

Set up the Smart Connect related information below.

Steering Trigger Condition

Band	2.4GHz	5GHz-1	5GHz-2
Bandwidth Utilization	<div><div></div></div> 0%	<div><div></div></div> 80%	<div><div></div></div> 0%
Enable Load Balance	<div><div></div>Yes<div></div>No</div>	<div><div></div>Yes<div></div>No</div>	<div><div></div>Yes<div></div>No</div>
RSSI	<div>Greater</div> <div>-58</div> <div>dBm</div>	<div>Less</div> <div>0</div> <div>dBm</div>	<div>Less</div> <div>0</div> <div>dBm</div>
PHY Rate Less	<div><div></div></div> Disable	<div><div></div></div> < 110 Mbps	<div><div></div></div> < 433 Mbps
PHY Rate Greater	<div><div></div></div> > 54 Mbps	<div><div></div></div> > 300 Mbps	<div><div></div></div> Disable
VHT	<div>All</div>	<div>All</div>	<div>All</div>

STA Selection Policy

RSSI	<div>Greater</div> <div>-58</div> <div>dBm</div>	<div>Less</div> <div>-76</div> <div>dBm</div>	<div>Less</div> <div>0</div> <div>dBm</div>
PHY Rate Less	<div><div></div></div> Disable	<div><div></div></div> < 110 Mbps	<div><div></div></div> < 433 Mbps
PHY Rate Greater	<div><div></div></div> > 54 Mbps	<div><div></div></div> > 300 Mbps	<div><div></div></div> Disable
VHT	<div>All</div>	<div>All</div>	<div>All</div>

Interface Select and Qualify Procedures

Target Band	<div>1: 5GHz-2</div> <div>2: 5GHz-1</div>	<div>1: 5GHz-2</div> <div>2: 2.4GHz</div>	<div>1: 5GHz-1</div> <div>2: 2.4GHz</div>
Bandwidth Utilization	<div><div></div></div> 0%	<div><div></div></div> 60%	<div><div></div></div> 0%

Bounce Detect